



| Item | QTY | Part Number    | Description                              | Material                              | Rev | Comments |
|------|-----|----------------|--|---------------------------------------|-----|----------|
| 6    | 1   | 53.25.13       | Rvs. hamerkopmoer M6 gecoat (27x13x4 mm) | Stainless Steel                       | B   |          |
| 5    | 1   | 53.47.71_A     | Rvs. bolkop Torx T30 M6x70 mm            | Stainless Steel, Austenitic [A2 - 80] | A   |          |
| 4    | 1   | 00.15.05       | Kst. klemveer paneelklem instelbaar      | Low Density Polyethylene              | B   |          |
| 3    | 1   | 72.15.97       | Verstelbare voet eindklem B=50           | Aluminum [EN AW-6060 T66]             | B   |          |
| 2    | 1   | 72.15.96 28-50 | Geanod. klemplaat eindklem 28-50mm /B=50 | Aluminum [EN AW-6060 T66]             | A   |          |
| 1    | 1   | 00.46.70       | Alu. Back Foot ValkPro+ P10° 80 mm z/p   | Aluminum [EN AW-6060 T66]             | A   |          |

|                      |  |  |                  |               |          |
|----------------------|--|--|------------------|---------------|----------|
| American projection: |  | Scale: 1:2                             | Author: V. Prins | Comments:     |          |
|                      |  | Unit: mm                               | Group:           |               |          |
|                      |  | Material:                              | Date: 2-7-2015   |               |          |
| Project:             |  |  |                  | Rev:          | State:   |
|                      |  |  |                  | A             | Released |
| Description:         |  | Alu. achter voet ValkPro+ P10° zijkant |                  | Part number.: | Size:    |
|                      |  |  |                  | 72.46.71      | A3       |

www.valksolarsystems.nl