

Datasheet

Roof Hooks - Tiles

VAN DER VALK



SOLAR SYSTEMS

Innovation House, Discovery Park
 Ramsgate Road, Sandwich CT13 9FF
 United Kingdom
 T +44 (0)1304 897658
 info@valksolarsystems.co.uk
 www.valksolarsystems.co.uk



Pitched Roof - Clamp - Standard Tile



Pitched Roof - Clamp - Standard Tile

Specifications

- Our pitched roof system has different fixation methods to different types of tiled roofs.
- There are roof hooks for standard tiles, plain tiles and slates.
- Standard hooks for portrait, and twist hooks for landscape panel mounting.
- Due to height adjustability in de roof hook, profiles can be mounted in a straight line.
- All roof hooks are made of stainless steel.
- Pre-mounted with hamerhead bolt and surration nut.
- Side mounting for easy and fast installation.
- Special screws with special tip for strong fixation.

Article overview

Standard roof	
USP	High flexibility standard due to 3-way adjustability
Article number	747844
Description	Stainless steel roof hook - adjustable side
Strength	855 N
Adjustability top	27 mm
Adjustability bottom	13 mm
Adjustability width	50 mm
Min. batten distance	65 mm
Article number	747845
Description	Stainless steel roof hook - adjustable side twist
Strength	855 N
Adjustability top	27 mm
Adjustability bottom	13 mm
Adjustability width	50 mm
Min. batten distance	65 mm
Slate roof	
USP	Specially designed for specific roof measurements
Article number	747872
Description	Stainless steel roof hook - slate side
Strength	335 N
Adjustability	21 mm
Min. batten distance	88 mm
Article number	747873
Description	Stainless steel roof hook - slate side twist
Strength	335 N
Adjustability	21 mm
Min. batten distance	88 mm
Article number	747878
Description	Flashing set slate hook, consists of: 1x flashing 365 x 365 mm, 1x bag with foam and 2 wooden shims, 3x hall hook



Datasheet

Roof Hooks - Tiles

VAN DER VALK



SOLAR SYSTEMS

Innovation House, Discovery Park
Ramsgate Road, Sandwich CT13 9FF
United Kingdom

T +44 (0)1304 897658

info@valksolarsystems.co.uk

www.valksolarsystems.co.uk



Pitched Roof - Clamp - Standard Tile



Pitched Roof - Clamp - Standard Tile

Article overview

Plain tile roof	
USP	Compact 'foot' for small batten distance
Article number	747867
Description	Stainless steel roof hook - plain tile side
Strength	290 N
Adjustability	21 mm
Min. batten distance	46 mm
Article number	747868
Description	Stainless steel roof hook - plain tile side twist
Strength	290 N
Adjustability	21 mm
Min. batten distance	46 mm



Fixation material

Torx-screw	
USP	Special tip and thread for easy and strong fixation
Article number	773360
Description	Stainless steel torx-screw T30
Measurements	5,5 x 58 (thread: 36 mm)



Measurements

